



Polished Millstone Fountain | Installation Information

If you are thinking about buying or installing a Polished Millstone Fountain, here are all the components you need for a simple, recirculating set-up. Let's take a closer look at how this works:

One | [Polished Millstone](#)

Two | Accessories - There are 3 basic components we sell individually that complete the setup:



1. FOUNTAIN INSTALLATION RESERVOIR, 58 INCH this holds the water under the fountain, think of this as a hidden pool. It holds approximately 65 gallons of water. Installation requires concrete. [More information.](#)



2. SUBMERSIBLE PUMP, 1320GPH submersible pump (plugs into a 110V electrical outlet) The pump is connected to flexible hosing that pushes the water up through the fountain. We recommend the outlet be no closer to the reservoir than 4 feet. This pump is offered in 10 foot electric cord length, plan accordingly. [More information.](#)



3. PEBBLES, Eleven (11) bags of our Mexican Beach Pebbles will be required for this installation. This will cover 44 square feet. They hide the reservoir underneath for a seamless, "disappearing" effect. [More information.](#)

Three | Location Find a nice spot in your yard where you'd like to showcase your snazzy new fountain. You'll be digging a hole into the dirt in this area, so make sure it's not a hard surface like a patio or concrete pad (unless you love jack-hammering!), or an extremely root-ridden area right next to an ancient, gnarly tree.

Installation Guide

First install the Fountain Installation Reservoir 58" Kit with provided installation instructions. [More information.](#)

- Once your reservoir is installed double check to make sure it is level. Put the pump in the reservoir. Place the pump access door on the side nearest the power supply. Run the pump power cord out the side, under the edge of the cover. Put all covers in place.
- Place the stone fountain pedestal in the center of the reservoir lining up the drillhole with the center hole on top of the reservoir. Level using plastic shims.
- Set the millstone on top of the stone pedestal. Line up the center drill holes of the millstone and pedestal. Using plastic shims, level the fountain between the millstone and pedestal.
- Next, push the hose down, plug side up, through the drill holes. The plug should seal flush at the top of the millstone.
- Once the millstone is in place (and level) reach into the reservoir and pull the hose end to connect it to the pump. Hide or bury the pump's electric cord as necessary (or as advised by your electrician).
- Fill your reservoir with water, plug the pump in. View the waterflow. You may have to shim between the millstone and the pedestal one last time to get full, even water coverage. Add [mineral and algae additives](#) to the water (may be purchased through us). Cover the reservoir with the smooth beach pebbles.



VOILA! Grab a drink and lounge chair. Prepare to be relaxed by the soothing sounds of your new fountain.